



*"Speed, Flexibility, Dependable Performance"*

T1322OCS  
T1432OCS

## Overhead Compression Tunnel



MADE IN U.S.A

Distributed by:



Forest Hill, Maryland 21050  
Telephone: 410-893-3307  
Visit Our Website: [www.inopakinc.com](http://www.inopakinc.com)  
Email: [sales@inopakinc.com](mailto:sales@inopakinc.com)



**TEXWRAP**®

525 Vossbrink Drive · Washington, MO 63090  
Ph (636)239-7424 · Fax (636) 239-7322  
[sales@texwrap.com](mailto:sales@texwrap.com) · [www.texwrap.com](http://www.texwrap.com)

## Features, Functions & Benefits

- Quad jackshaft supported top belt
- Adjustable slope on belt
- AC motor on top belt
- AC motor height adjustment
- Remote pendant for height adjustment control
- Continuous duty industrial grade blower motor
- Top/bottom adjustable air control dampers for controlled shrink results
- Easy to read L.E.D. display
- Cool-Touch energy efficient design
- DC motor with variable speed control for conveyor speed
- Top air velocity control for the adjustment of air flow to the top or bottom of the package for even shrink
- Audible high heat alarm and high heat limit thermostat
- Stainless steel mesh belt
- Durable powder coated finish

Specifications:	T1322OCS	T1432OCS
Chamber Opening:	13"H x 22"W	14"H x 32"W
Chamber Length:	38"L	55"L
Electrical:	240V, 45 amp, 3 phase	240V, 55 amp, 3 phase
Heaters:	3 flange cal-rod type	3 flange cal-rod type
Conveyor Height:	Adj. from 30" to 35"	Adj. from 30" to 35"
Conveyor Speed:	0 - 100 FPM	0 - 100 FPM
Conveyor Width:	15"	24"
Footprint:	58"L x 46"W x 77-82"H	104"L x 56"W x 77-82"H
Shipping Weight:	1,400 lbs	1,700 lbs

	T1322OCS	T1432OCS
<b>A=</b>	40"	53"
<b>B=</b>	32.25"	42.25"
<b>C=</b>	58"	103.5"
<b>D=</b>	77 - 82"	77 - 82"
<b>E=</b>	30"	30"
<b>F=</b>	46"	56"

